



J2 Cable Lasher - Known for Its Durability

The J2 Cable Lasher is used to lash an overhead cable or numerous cables to a supporting strand or to an existing lashed cable with stainless steel lashing wire.

The J2 Lasher's design also gives it maximum service life. The body is cylindrical to help it slip more easily through branches and obstructions. There is a built-in mechanical brake to prevent unintended reversal, an automatic drum lock for easy span transfers, an all-range tensioning device for optimum strand traction and high strength front and rear gates for tighter lashing.

- ▶ Will lash any single or multiple overhead cables up to 3 in. (76 mm) diameter across on any suspension strand from 1/4 in. (6 mm) to 7/16 in. (11 mm). A factory modification will allow the lasher to accommodate .535 in. (13 mm) strand if necessary.
- ▶ Each of two recessed magazines will hold a 1200 ft. coil of .045 in. (365 m of 1 mm wire) lashing wire (or 450 ft. of .065 in.). The Lashing Wire is fully recessed and covered by a gate.
- ▶ J2 Lashers make overlapping easy. Just push down on the strand lock, rotate it a quarter turn to disengage and you can overlap additional cables together on previously lashed cable
- ▶ Positive internal gear-to-gear mechanism has no chains or belts to stretch, slip or break
- ▶ Pre-drilled and tapped at the factory for mounting of the lasher guard or "halo". For use when lashing in overgrown areas.
- ▶ The lasher is furnished with a rugged lightweight storage chest with corrosion resistant hardware, recessed latches and a moisture-proof, tongue-in-groove for maximum protection when not in use
- ▶ Supplied with a 6 ft. bridle rope assembly and snap hooks, and an information and operation manual



P/N	Description	Wire Dia.	Weight
86070	J2 Cable Lasher Standard w/ Chest	.045	65 lbs. (30 kgs)
86071	J2 Cable Lasher w/ Chest <i>Modified for 450 ft. (optional)</i> Weight of lasher only	.065	65 lbs. (30 kgs) 46 lbs. (21 kgs)
86072	J2 Cable Lasher <i>Modified for .535 in. strand</i>		65 lbs. (30 kgs)
86074	J2 Cable Lasher <i>w/o strand lock</i>		65 lbs. (30 kgs)
03165	Bridle Rope Assembly only		3 lbs. (1.4 kg)
08189	Chest only		19 lbs. (8.6 kgs)
70190	Towing Lanyard 35 ft. (10.7 M) (optional)		6 lbs. (2.7 kgs)
70012	Lasher Guard "Halo" (optional)		3 lbs. (1.4 kg)