



## Modular Plugs

These rugged, dependable plugs are specially manufactured to exacting GMP standards for highest possible quality and performance.

- ▶ Each UL-listed plug is molded from fire-resistant, translucent polycarbonate that's either clear or color tinted for fast application identification

*Note: High gold content in a modular plug is the key to corrosion resistance.*

- ▶ The gold, extra-conductive, corrosion-resistant mating surface helps minimize contact abrasion during insertion and removal

### For Tinsel/Stranded Cordage:

Insulated conductor diameter: .038 in. (.96 mm)  
Clear Plugs, Weight: 1 lb. (454 g)

P/N	Configuration
17074	4-Contact x 4-position (4 x 4) handset plugs 100/pkg.
17078	2-Contact x 6-position (2 x 6) RJ11 line cord plugs 100/pkg.
17075	4-Contact x 6-position (4 x 6) RJ11 line cord plugs 100/pkg.
17076	6-Contact x 6-position (6 x 6) RJ11 line cord plugs 100/pkg.
17077	8-Contact x 8-position (8 x 8) RJ45 non-keyed line cord plugs 100/pkg.
17043	8-Contact x 8-position (8 x 8) RJ45 keyed line cord plugs 100/pkg.
25125	10-Contact x 10-position (10 x 10) RJ45 keyed left line cord plugs 25/pkg.
25126	10-Contact x 10-position (10 x 10) RJ45 keyed right line cord plugs 25/pkg.
25127	10-Contact x 10-position (10 x 10) RJ45 non-keyed line cord plugs 25/pkg.

### For Solid Wire:

Insulated conductor diameter: .038 in. (.96 mm)  
Grey Plugs, 100/pkg. Weight: 1 lb. (454 g)

24061	3-Pair 22/24 AWG RJ11 plugs
24062	4-Pair 22/24 AWG RJ45 plugs

### For D Inside Wire & Plenum:

Insulated conductor diameter: .038 in. (.96 mm)  
Blue Plugs, 100/pkg. Weight: 1 lb. (454 g)

17187	3-Pair 24 AWG RJ11 plugs
17188	4-Pair 24 AWG RJ45 plugs

### For Shielded Twisted Pair (STP):

Insulated conductor diameter: .038 in. (.96 mm)  
Clear/Metallic Plugs, 25/pkg. Weight: 4 oz. (113 g)

24042	4-Pair RJ45 STP plugs
-------	-----------------------

### For Category 6 Unshielded Twisted Pair (UTP):

Insulated conductor diameter: .042 in. (1.06 mm)  
Clear Plugs, 100/pkg. Weight: 1 lb. (454 g)

24065	8-Contact Cat. 6 plug with separate conductor alignment bar for precise wire loading
-------	--

### For DEC Data Cable:

Insulated conductor diameter: .040 in. (1.00 mm)  
Clear Plugs, 100/pkg. Weight: 1 lb. (454 g)

17090	6-Contact x 6-position MMJ plug
-------	---------------------------------



## Modular Cordage

The perfect accessory to our Modular Plugs, this high quality, standard, flat, oval line cord is available in four, six, and eight conductors. The cordage is conveniently supplied on 1000-ft. coils for use with our Terminal Wire Reel (80470).

- ▶ The outer jacket is made of lustrous, silver satin PVC for tough, fire resistant flexible insulation. The jacket is also raised on one side for simplified identification when pressing.
- ▶ Each 26 AWG conductor is composed of seven 36 AWG copper strands for strength and high conductivity, with color-coded insulation for fast lead identification

P/N	Description	Weight
15394	Four-conductor line cordage	10 lbs. (4.54 kg/coil)
15395	Six-conductor line cordage	15 lbs. (6.80 kg/coil)
15396	Eight-conductor line cordage	20 lbs. (9.07 kg/coil)

