

Bonding Ribbon

Used to permanently bond the sleeves or sheath of cables in manholes, bonding ribbon is supplied on 5 lbs. (2.3 kgs) spools

- ▶ It is made of annealed copper with a smooth continuous tin coating
- ▶ Measures 1/16 in. (1.6 mm) thick x 3/8 in. (9.5 mm) wide and roughly 65 ft. (19.8 M) long

P/N 68681 Weight: 5 lbs. (2.3 kgs)



Bonding Ribbon Clamp

This lead antimony clamp, along with 3/16 in. x 7/8 in. hammer drive anchors, lets you quickly attach Bonding Ribbon (P/N 68681) to the manhole wall or roof. The clamp has a 9/16 in. (14 mm) opening for inserting the anchor. They are sold in packages of 100.

P/N 06567 Weight: 2.5 lbs. (1.1 kg)/pk.

B Temporary Bond

A handy connection for temporarily grounding any conductive object in your work area which could become energized if a fault developed .

- ▶ The bond consists of a 5 ft. (152 cm) copper strand and a rubber-covered cord with battery clips on each end
- ▶ Just attach the small clip to a suspension strand and the large clip to the object you want to ground; if a fault develops, the cord's insulation will begin to smoke

P/N 07781 Weight: 1 lb. (.45 kg)

