

This integrated group of specialized tools for working with lead-sheathed cable is probably the most complete selection you can find. From furnaces and regulators to pots and hooks, GMP has everything you need to handle your lead cable network efficiently.



Propane Furnace

Used to heat materials used in splicing operations.

- ▶ This efficient solder melting furnace delivers a hefty 43,200 BTU output on just 2 lbs./hour of conventional propane

To set up the Furnace for use connect the Pressure Regulator (70118) to the LP Gas Cylinder (70123) and the LP Gas Hose (76790) to the Regulator and Furnace. Use a Regulator Wrench (07516) to tighten all connections.

Do not use a furnace inside a manhole or tent.

P/N 70116 10 in. (25 cm) H x 8-1/2 in. (22 cm) dia.
Weight: 9 lbs. 12 oz. (4.4 kgs)

P/N 70117 Furnace Windshield
Weight: 1 lb. (.45 kgs.)

Pressure Regulator

This UL listed, all-brass unit works with LP torches and furnaces during heating operations.

- ▶ There's a 0-60 psi outlet pressure gauge, and you can adjust the pressure 5-60 psi
- ▶ Included are a POL inlet gland and nut (CGA 510), 1/4 in. (6 mm) dia. NPT opening, and a 9/16-18 LH hose outlet

P/N 70118 Weight: 2 lbs. (.91 kg)



LP Gas Hose

Ideal for connecting a propane pressure regulator outlet to a propane-powered heater, ventilator or engine inlet.

- ▶ This hose features a petroleum and gas resistant rubber inner tube, an overlaying cotton or synthetic fiber and rubber outer jacket
- ▶ Both ends have a spring guarded coupling.
- ▶ Is available in both 10 ft. (305 cm) and 30 ft. (914 cm) lengths
- ▶ OD: 5/8 in. (16 mm). ID: 1/4 in. (6 mm)



P/N	Description	Weight
76790	10 ft. length	2 lbs. 5 oz. (1 kg)
76791	30 ft. length	6 lbs. 14 oz. (3.1 kgs)

GENERAL TOOLS

TOOLS BUILT TO GO THE DISTANCE