



E Fuel Gas Hose



D Fuel Gas Hose

### D & E Fuel Gas Hoses

Designed for conveying fuel gas (Acetylene, MAPP or LP) from cylinder regulators to torches or gas appliances such as heaters or furnaces.

- ▶ D hose is made from RMA/CGA IP-7-1990 grade T fuel gas hose. It is reinforced hose of 3/16 in. ID 7/16 in. o.d. with a minimum bursting strength of 600 psi.
- ▶ The hose is equipped at both ends with a spring guard to prevent kinking near the fittings
- ▶ D hose is fitted with CGA #21 3/8-24 UNF left-hand gas-tight brass female couplings with a 9/16 in. external hex
- ▶ E hose is 1/4 in. bore, 5/8 in. O.D. and is designed for use with LP gas and is UL rated.
- ▶ E hose is fitted with CGA #23 0/16-18 UNF left-hand gas-tight brass female couplings with an 11/16 in. external hex.

#### Length and Hose Type

P/N	Length	Item
76780	6 ft. (1.8 M)	D Hoses
76781	8 ft. (2.4 M)	D Hoses
76783	12-1/2 ft. (3.7 M)	D Hoses
76784	25 ft. (7.5 M)	D Hoses
76790	10ft. (3M)	E Hoses
76791	30 ft. (9M)	E Hoses

