



Sealing Clamps

Used to secure wrapped joints while splicing plastic-sheathed, gas-tight cable, these 3/8 in. (9.5 mm) wide stainless steel clamps come in a variety of sizes to fit all common cable types.

- ▶ Each clamp consists of a perforated metal band that passes through a worm screw housing
- ▶ Below are our most popular sizes; however please contact GMP directly for a size not listed

P/N	Length	Weight
77401	For cable up to 1-1/16 in. (27 mm)	2 oz. (.06 kg)
77402	For cable up to 1-3/4 in. (44.5 mm)	2 oz. (.06 kg)
77403	For cable up to 2 in. (51 mm)	2 oz. (.06 kg)
77404	For cable up to 4 in. (102 mm)	2 oz. (.06 kg)
77405	For cable up to 6 in. (153 mm)	3 oz. (.09 kg)

C & D Pressure Flanges and Plugs

These handy flanges are useful when working with lead sheath cable.

- ▶ They're made from tinned bronze and are sealed with a C Pressure Flange Plug
- ▶ Each flange has an overall diameter of 5/8 in. (16 mm) and 1/8 in. internal pipe thread. The D Pressure Flange has an extra 1/8 in. of external thread on the bottom.
- ▶ The C Pressure Flange Plug is a hex head brass plug with 1/8 in. pipe threads
- ▶ Both the C and D Pressure Flanges and the C Pressure Flange Plugs are sold in packages of 25 pcs



P/N	Description	Weight
75481	C Pressure Flange 25/pk.	8 oz. (.23 kg)/pk.
75482	C Pressure Flange Plug 25/pk.	8 oz. (.23 kg)/pk.
75483	D Pressure Flange 25/pk.	8 oz. (.23 kg)/pk.

TOOLS BUILT TO GO the DISTANCE



F Pressure Flange

This combination flange and fitting is ideally suited for use at pressure reading points, bypasses or air inlets at any 3/4 in. (19 mm) dia. or larger cable.

- ▶ The flange's 1/8 in. female pipe thread can accept a wide range of fittings
- ▶ The assembly can be used with any standard valve, tee or elbow with a 1/8 in. male NPT thread
- ▶ Two Sealing Clamps are needed for each flange you want to install

P/N 08669 10 to a package Weight: 15 oz. (.42 kg)