



Universal Sheave Block (Non-Swiveling)

The Universal Sheave Block when used with an Overhanging Floor Socket 70249 permits cable pulls upward, downward, or sideways without the use of snatch blocks. The assembly consists of a specially designed sheave with two square shanks which lock into the Overhanging Floor Socket, fastened to the rear deck of the truck body. When an upward pull is desired, the bottom shank is locked into the socket. For a side pull, the side shank is used.

P/N 70234 Material is cast steel ASTM A27, Class 65-35
Weight: 45 lbs. (20 kgs)

TOOLS
GO
DISTANCE



Overhanging Socket

Floor Sockets

Available in both Overhanging and Floor Types, these sockets give you a secure way to mount and use the Universal Sheave Block.

- ▶ Overhanging Socket is fastened to the rear deck of the truck body to the rear cross channel. It is supplied with a removable 5/8 in. x 5 in. "SL" connecting pin to hold attachments in place, Universal Sheave Block. Material: Cast Steel ASTM A27, Class 65-35.
- ▶ Star Shaped Floor Socket is mounted flush to the body deck forward of the rear cross channel of the truck. It holds the Universal Sheave in the usual position or at a 45° angle when required. It is supplied with a removable 5/8 in. x 5 in. "SL" connecting pin to hold attachments in place, Universal Sheave Block.

P/N 70249 Overhanging Socket Weight: 28 lbs. (12 kgs)

P/N 70250 Star Shaped Floor Socket Weight: 24 lbs. (11 kgs)



Star Shaped Floor Socket