

Sealing Tape & Cord

This pliable black butyl rubber material is ideal for building up seal collars and filling cavities in splice cases, or sealing bond clamps, ground conductors and the hardware used in cable splicing.

The product is provided in 2 forms: tape and cord.

P/N	Description	Weight
76001	Cord - .305 in. (7.7 mm) dia x 15 ft. (4.6 m) L	13 oz. (.37 kgs)
76011	Tape - .125 in. (3.2 mm) Thick x 1.50 in. (38 mm) Wide x 15 ft. (4.6 m) L	1lb. 8 oz. (.68 kgs)



CR Tape

This two-ply blanket tape makes a perfect temporary covering and moisture seal while you're splicing, repairing or jointing insulated cable, or working on temporary gas-filled splices.

The .030 in. (.76 mm) thick, light-colored, unvulcanized tacky face is permanently bonded to a layer of .020 in. (.51 mm) thick non-tacky black vulcanized rubber.

A removable Holland cloth covers the tacky side until you're ready to use the tape.

Not only does it have exceptionally high 25 lbs./sq. in. (4.4 kg/cm²) tensile strength, 400% Minimum/750% Maximum elongation, and 350 Volts/mil (1380 V/.01mm) dielectric strength, the tape's excellent cohesion, weathering and plasticity characteristics make it easy to create fast, durable, air-tight and gas proof seals by hand.

P/N	Description	Weight
71440	28 in. (711 mm) W x 20 ft. (6.1 m) L	18 lbs. (8.16 kgs)
71441	36 in. (914 mm) W x 20 ft. (6.1 m) L	24 lbs. (11 kgs)

Muslin Roll

This first quality, plain-woven fabric is used for initial wrapping of cable splices. It is made from unbleached cotton sheeting with a high 52 x 32 thread count.

We offer three sizes of muslin roll along with a special 36 in. (91.4 cm) wide bolt that is available by special request.

P/N	Description	Weight
67272	2 in. (51 mm) W x 12 ft. (3.7 m) L	12 oz. (.34 kg)/pk 10 rolls/pk.
67274	4 in. (102 mm) W x 24 ft. (7.4 m) L	2 lbs. (.91 kg)/pk 10 rolls/pk
67276	6 in. (153 mm) W x 24 ft. (7.4 m) L	5 lbs. (2.3 kgs)/pk 8 rolls/pk.

