



### B Lashing Wire Remover

This 32 in. (812 mm) tool makes removing lashing wire from any 3 in. (76 mm) diameter or smaller overhead cable quick and easy.

- ▶ Tapered split steel rod fits around the strand, while the steel saddle travels along behind it on the strand and cable, stabilizing and guiding the tool as it unravels the wire
- ▶ Features two roller assemblies: the upper one is for the strand, while the lower one is for the cable
- ▶ A hinged gate on the lower roller simplifies mounting and removal
- ▶ All parts are zinc plated for extra corrosion resistance
- ▶ Rope sling included with the tool

To free a lashed cable, just mount the remover on your strand, then pull it forward using the rope sling included with the tool.

P/N 07621 Weight: 7 lbs. 8 oz. (3.54 kgs)



### E Lashing Wire Clamp

Designed for permanent wire terminations, this clamp has the same hardware, construction and clamping range as our D Clamp, but with a one piece stamping formed to let both sides grip the messenger in perfect alignment. We also supply an oversize E lashing Wire Clamp for strand up to 9/16 in. (14 mm)

P/N	Description	Weight
81460	E Lashing Wire Clamp 7/16 in. (11 mm) opening	6 lbs. (2.7 kgs) (100 /carton)
81461	Oversize E Lashing Wire Clamp 9/16 in. (14 mm) opening	6 lbs. (2.7 kgs) (100 /carton)

### D Lashing Wire Clamp

Perfect for temporary and permanent terminations or grounds, this all steel clamp lets you securely attach two lashing wires or #6 ground wire on any size strand from 1/4 in. to 7/16 in. (6-11 mm) diameter.

- ▶ Two grooved plates fit on opposite sides of the strand
- ▶ Plates secured by a threaded stud with a flanged shoulder and washer to block slippage, and two hexagonal nuts: one on the long end of the stud to tighten the clamp, one on the other end to terminate the wire against the two washers
- ▶ A mechanically galvanized finish provides extra corrosion resistance

P/N 07886 Weight: 15 lbs. (6.8 kgs) /100 per carton

