



B Lifting Shackle

Allows attachment of a chain hoist to lashed overhead cable for lifting.

- ▶ A flat steel shackle fits between strand and cable
- ▶ Captive locking pin clevis to attach chain hoist hook
- ▶ Can handle loads up to 3000 lbs. (1360 kgs)

P/N 07560 Weight: 9 oz. (.25 kg)

Strand Pullers

This forged steel unit is used when pulling or tensioning suspension strand. The L, H, and B Strand Pullers feature a fixed and movable jaw linked to a clevis. Applying pull to the clevis causes the jaw in turn to grip the strand.

- ▶ The B Strand Puller is designed for tensioning figure-8 cable on 1/4 in. (6 mm) poly jacketed strand, and designed for pulling loads up to 5000 lbs. (2268 kgs)
- ▶ The H Strand Puller is designed for tensioning strand sizes from 3/8 in. through 1/2 in. (9-13 mm) and for pulling loads that exceed 5000 lbs. but not more than 10,000 lbs. (4535 kgs)
- ▶ The L Strand Puller is designed for tensioning strand sizes from 3/16 in. through 7/16 in. (5-11 mm) and for pulling loads up to 5000 lbs. (2268 kgs)
- ▶ A safety chain permanently secured to a shackle acts as a safety tether in the event the grip disengages



P/N	Description	Weight
68490	B Strand Puller	6 lbs. (3 kgs)
68491	H Strand Puller	15 lbs. 8 oz. (7 kgs)
68492	L Strand Puller	6 lbs. 4 oz. (3 kgs)

Note: The gripping power of the strand puller is greatly reduced if either the grooves of the jaw or the strands are coated with oil, grease, or paraffin. For best results wipe both the strand at the point of attachment and the grooves of the puller jaws thoroughly with a cleaning solution.

Overhead Handline

Used by the craftsperson for raising or lowering tools and materials in OSP overhead work operations.

- ▶ The Overhead Handline consists of a supporting hook with integral one sheave block fitted with 60 ft. of 1/2 in. (18 m x 13 mm) manila rope
- ▶ The supporting hook is shaped to keep clear of the cable and is equipped with a handle having a keeper at one end to lock the hook to the strand on ring supported cable
- ▶ A metal link is provided to prevent disengagement of the block from the strand when the handline is used on lashed cable or self supporting cable
- ▶ Is furnished with a 24 in. (61 cm) length of chain with a shackle at one end and a snap hook at the other end
- ▶ An open hook at one end makes it easy to attach a bucket or tray to the line

P/N 68590 Weight: 7 lbs. (3.2 kgs)

