

**New
or
Improved**



D Cabinet Balcony

Our newest pole mounted work platform, the GMP D Cabinet Balcony was designed to accommodate the new generation of fiber optic based cabinets as well as the existing line of cross connect cabinets.

The 22 in. (559 mm) D x 30 in. (762 mm) W durable aluminum grate seat resists buildup of snow, water and debris while giving you secure footing.

The 36 in. (914 mm) H rear guard railing along with balcony entrance step on either side (or both sides with optional step), give

you extra safety and convenience. All frame parts are produced from hot-dipped galvanized steel or stainless steel for corrosion resistance.

P/N 79283 Weight: 93 lbs. (42 kgs)

P/N 29139 Extra Step Kit Weight: 2 lbs. (91 g)



SAFETY NOTE:

We at GMP do everything we can to make all our products as safe as possible. But no matter how safe we make them, there'll always be some risks inherent in working on exposed aerial installations.

To help minimize those risks, follow these simple tips, whenever you're working aloft.

Tethers: Always wear a body belt and safety strap when working aloft. It could mean the difference between a little embarrassment and a bad fall if your ladder or platform should fail.

Practices: Your utility company wrote them for one reason: to protect you! Be sure you know all the practices that apply to your work before you do it. It won't take long, it's easy to do, and it'll help protect you, your company and your community if something goes wrong.

AERIAL TOOLS

TOOLS
BUILT TO
GO THE
DISTANCE

B Cable Guards

These 8 in. (203 mm) long slit polyethylene tubes are available in four (4) different diameters to help prevent cable sheath abrasion where strand is attached to poles. Standard package 25.



P/N	Cable Diameter	Weight
74218	1/2 in. (13 mm)	1 lb. (.45 kg)/pkg.
74222	1 in. (25 mm)	1-1/2 lb. (.68 kg)/pkg.
74226	1-1/2 in. (38 mm)	2 lbs. (.90 kg)/pkg.
74228	2 in. (51 mm)	2-1/2 lbs. (1.13 kg)/pkg.