

GMP TORNADO MAINTENANCE SCHEDULE

PROCEDURE	DAILY	WEEKLY	MONTHLY
Clean all assemblies and components thoroughly			
Inspect hydraulic hoses for leaks and cracks			
Inspect fasteners, screws and retaining pins / wire			
Check / adjust chain tension			
Check tractor drive pads for wear / damage			
Clean air chamber			
Check / replace cord seals			
Check / replace cable seals			
Tire pressure / condition			
Check condition of emergency stop lead			
Clean rod infeed guide bracket and collets			
Clean measuring wheel measuring disc and speed pick up probe			
Function of electronic panel			
Oil the frame pivot points			
Grease jacking screw thread			
Oil air chamber adjusting screw			
Oil Oilite bearings with light machine oil			
Grease mounting frame axles			
Clean and lubricate chain*			
Clean and lubricate the chain support slide bars			
Check the condition of service and spare 12V DC battery			
Check condition of the compressed air hose			

* Should be more often if subjected to abnormal use and / or excessive contamination.



Recommended Chain Lube **METAFLUX CHAIN LUBRICANT**

This Chain Lubricant is a fully synthetic, special chain lubricant for use in lubrication of the Tornado's drive chain.

P/N 89153 Metaflux Chain Lubricant Weight: 13.5 oz. (400ml)

