

BLOWING MACHINE COMPARISON



	MicroDrive	Gentle Air	AccelAir 2	Whisper	Whisper Flat Drop	AirStream Pneumatic	AirStream	Hurricane	JetStream®	Tornado
Cable Diameter:	2.6 - 5mm (0.102 - 0.196")	1.0 - 3.0mm (0.039 - 0.118")	.8 - 3.0mm (.03 - .12")	2 - 8.5mm (.08 - .33")	call factory	2.5 - 11mm (.10 - .43")	2.5 - 11mm (.10 - .43")	2.5 - 14mm (.10 - .55")	³ 4 - 20mm (.6 - .79")	¹ 5.84 - 34mm (.23 - 1.34")
Tube Size (O.D.):	7.0, 8.0, 8.5, 10.0, 12.0, 12.7, 14.0mm	4 to 7mm (0.158 to 0.275")	3 - 10mm (.12 - .40")	4 - 18mm (.15 - .63")	4 - 18mm (.15 - .63")	5-18mm (.20-.71")	5-18mm (.20-.71")	5 - 25mm (.20 - .98")	10 - 50mm O.D. (.75 - 1.50" SDR)	12 - 63mm O.D. (.75 - 2.00" SDR)
Flat Drop Compatible	No	No	No	Yes with optional kit	Yes	Yes	Yes	No	No	No
EABF® Compatible	Yes	No	No	No	No	No	No	No	No	No
Cable Speed (Adjustable):	0 - 300 ft/min (0 - 90 m/min)	0 - 300 ft/min (0 - 90 m/min)	0 - 165 ft/min (0 - 50 m/min) with buckle detection 0 - 328 ft/min (0 - 100 m/min) without buckle detection	0 - 300 ft/min (0 - 90 m/min)	0 - 300 ft/min (0 - 90 m/min)	0 - 262 ft/min (0 - 80 m/min)	0 - 262 ft/min (0 - 80 m/min)	0 - 280 ft/min (0 - 85m/min)	0 - 280 ft/min (0 - 85 m/min)	0 - 300 ft/min (0 - 90 m/min)
Max Air Pressure/ Volume:	220 psi (15 bar) 35 cfm (1 m³/min)	220 psi (15 bar) 35 cfm (1 m³/min)	220 psi (15 bar) 8.5 cfm (.24 m³/min)	220 psi (15 bar) 35 cfm (1 m³/min)	220 psi (15 bar) 35 cfm (1 m³/min)	220 psi (15 bar) >53 cfm (1.5m³/min)	220 psi (15 bar) 35 cfm (1 m³/min)	220 psi (15 bar) 150 - 450 cfm (12 m³/min)	² 220 psi (15 bar) 150 - 450 cfm (12 m³/min)	² 175 psi (12 bar) 150 - 450 cfm (4 - 12 m³/min)
Drive:	Drive Wheel	Drive Roller	Drive Wheel	Drive Roller	Drive Roller	Belts	Belts	Belts	Belts	Belts
Power:	Vari Speed Drill	Vari Speed Drill	110/220 VAC or Battery	Vari Speed Drill	Vari Speed Drill	Pneumatic	110/220 VAC	110/220 VAC	Gas/Hydraulic	Gas/Hydraulic
Cable Safety	Magnetic Torque Control	Friction Torque Control	Buckle Protection	Torque Control via Drill	Torque Control via Drill	Torque Control	Electronic Torque Control	Electronic Torque Control	Hydraulic Pressure Sensing	Hydraulic Pressure Sensing
Length:	5.6" (143mm)	9.7" (246mm)	4.7" (120mm)	9.7" (246mm)	9.7" (246mm)	18" (460mm)	18.1" (460mm)	21.6" (550mm)	24.5" (620mm)	42" (1070mm)
Width:	9.7" (248mm)	8.1" (206mm)	7.2" (184mm)	8.1" (206mm)	8.1" (206mm)	11.8" (300mm)	11.8" (300mm)	12.2" (310mm)	19" (484mm)	27" (690mm)
Height:	6.6" (169mm)	8.5" (216mm)	6.5" (166mm)	8.5" (216mm)	8.5" (216mm)	9.4" (240mm)	10.6" (270mm)	13.8" (350mm)	9.2" (233mm)	48.5" (1230mm)
Weight:	6 lbs. (3.1kg)	12 lbs. (5.4kg)	6.6 lbs. (3kg)	12 lbs. (5.4kg)	12 lbs. (5.4kg)	31 lbs. (14kg)	33 lbs. (15kg)	53 lbs. (24kg)	68 lbs. (31kg)	155 lbs. (70kg)
Part Number – Std.	89850	89916	89500	89910	89915	89297	89300	90000	89950	89000
Part Number – Plus		89901	89860	89897	89895		89321	90055	90058	89099
Part Number – Max								90054		89113

Standard outfitted blowers come with 1 cable and seal size
Plus outfitted blowers come with 3 cable and seal sizes
Max outfitted blowers come with every available cable and seal size

Up to 30% savings on accessories
when purchasing the Plus or Max

- ¹ Micro duct (10 & 12mm O.D.) blowing available with add-on kit
- ² Airflow is duct size dependent
- ³ 4 - 6mm fiber possible with dedicated belt

