



BLOWING MACHINE COMPARISON



| | MicroDrive | Gentle Air | AccelAir 2 | Whisper | Whisper Flat Drop | AirStream | Hurricane | JetStream® | Tornado |
|----------------------------------|--|--|---|--|--|--|--|---|---|
| Cable Diameter: | 2.6 - 5mm (0.102 - 0.196") | 1.0 - 3.0mm (0.039 - 0.118") | .8 - 3.0mm (.03 - .12") | 3 - 8.5mm (.11 - .33") | call factory | 2.5 - 11mm (.10 - .43") | 2.5 - 14mm (.10 - .55") | ³ 4 - 20mm (.16 - .79") | ¹ 5.84 - 34mm (.23 - 1.34") |
| Tube Size (O.D.): | 7.0, 8.0, 8.5, 10.0, 12.0, 12.7, 14.0mm | 4 to 7mm (0.158 to 0.275") | 3 - 10mm (.12 - .40") | 4 - 18mm (.15 - .63") | 4 - 18mm (.15 - .63") | 5-18mm (.20 - .71") | 5 - 25mm (.20 - .98") | 10 - 50mm O.D. (.75 - 1.50" SDR) | 12 - 63mm O.D. (.75 - 2.00" SDR) |
| Flat Drop Compatible | No | No | No | Yes with optional kit | Yes | Yes | No | No | No |
| EABF® Compatible | Yes | No | No | No | No | No | No | No | No |
| Cable Speed (Adjustable): | 0 - 300 ft/min (0 - 90 m/min) | 0 - 300 ft/min (0 - 90 m/min) | 0 - 165 ft/min (0 - 50 m/min) with buckle detection 0 - 328 ft/min (0 - 100 m/min) no buckle detection | 0 - 300 ft/min (0 - 90 m/min) | 0 - 300 ft/min (0 - 90 m/min) | 0 - 262 ft/min (0 - 80 m/min) | 0 - 280 ft/min (0 - 85m/min) | 0 - 280 ft/min (0 - 85 m/min) | 0 - 300 ft/min (0 - 90 m/min) |
| Max Air Pressure/ Volume: | 220 psi (15 bar) 35 cfm (1 m³/min) | 220 psi (15 bar) 35 cfm (1 m³/min) | 220 psi (15 bar) 8.5 cfm (.24 m³/min) | 220 psi (15 bar) 35 cfm (1 m³/min) | 220 psi (15 bar) 35 cfm (1 m³/min) | 220 psi (15 bar) 35 cfm (1 m³/min) | 220 psi (15 bar) 150 - 450 cfm (12 m³/min) | ² 220 psi (15 bar) 150 - 450 cfm (12 m³/min) | ² 175 psi (12 bar) 150 - 450 cfm (4 - 12 m³/min) |
| Drive: | Drive Wheel | Drive Roller | Drive Wheel | Drive Roller | Drive Roller | Belts | Belts | Belts | Belts |
| Power: | Vari Speed Drill | Vari Speed Drill | 110/220 VAC or Battery | Vari Speed Drill | Vari Speed Drill | 110/220 VAC | 110/220 VAC | Gas/Hydraulic | Gas/Hydraulic |
| Cable Safety | Magnetic Torque Control | Friction Torque Control | Buckle Protection | Torque Control via Drill | Torque Control via Drill | Electronic Torque Control | Electronic Torque Control | Hydraulic Pressure Sensing | Hydraulic Pressure Sensing |
| Length: | 5.6" (143mm) | 9.7" (246mm) | 4.7" (120mm) | 9.7" (246mm) | 9.7" (246mm) | 18.1" (460mm) | 21.6" (550mm) | 24.5" (620mm) | 42" (1070mm) |
| Width: | 9.7" (248mm) | 8.1" (206mm) | 7.2" (184mm) | 8.1" (206mm) | 8.1" (206mm) | 11.8" (300mm) | 12.2" (310mm) | 19" (484mm) | 27" (690mm) |
| Height: | 6.6" (169mm) | 8.5" (216mm) | 6.5" (166mm) | 8.5" (216mm) | 8.5" (216mm) | 10.6" (270mm) | 13.8" (350mm) | 9.2" (233mm) | 48.5" (1230mm) |
| Weight: | 6 lbs. (3.1kg) | 12 lbs. (5.4kg) | 6.6 lbs. (3kg) | 12 lbs. (5.4kg) | 12 lbs. (5.4kg) | 33 lbs. (15kg) | 53 lbs. (24kg) | 68 lbs. (31kg) | 155 lbs. (70kg) |
| Part Number – Std. | 89850 | 89916 | 89500 | 89910 | 89915 | 89300 | 90000 | 89950 | 89000 |
| Part Number – Plus | ----- | 89901 | 89860 | 89897 | 89895 | 89321 | 90055 | 90058 | 89099 |
| Part Number – Max | ----- | ----- | ----- | 90064 | ----- | 89327 | 90054 | 90059 | 89113 |

Standard outfitted blowers come with 1 cable and seal size
Plus outfitted blowers come with 3 most popular cable and seal sizes
Max outfitted blowers come with every available cable and seal size

- ¹ Micro duct (10 & 12mm O.D.) blowing available with add-on kit
- ² Airflow is duct size dependent
- ³ 4 - 6mm fiber possible with dedicated belt