4, 6 AND 9 BOLT POCKETBOOK GRIPS

4 Bolt Pocketbook Grip



6 Bolt Pocketbook Grip



9 Bolt Pocketbook Grip



FEATURES:

Weight: 10.5 lbsLength: 21.25 inch

 Max tension limit: 5,000 lbs or 50 percent of rated strength of conductor, whichever is smaller.

Custom milled to: .360-.875 inch dia.

Bolt size: 1/2 inch steel
Bale: 1/2 inch steel
Final Torque: 40 ft-lb
Body: Extruded aluminum

Weight: 10.5 lbs. (4.76kg)

P/N 74153-0360 4 Bolt Pocketbook Grip

FEATURES:

Weight: 27 lbsLength: 30.1 inch

 Max tension limit: 12,000 lbs or 50 percent of rated strength of conductor, whichever is smaller.

whichever is smaller.

Custom milled to: .415-1.250 inch dia.

Bolt size: 5/8 inch steel
Bale: 5/8 inch steel
Final Torque: 60 ft-lb
Body: Extruded aluminum
Weight: 27.0 lbs. (12.25kg)

P/N 74154-0415 6 Bolt Pocketbook Grip

FEATURES:

• Weight: 67-68 lbs

Length: 41 inch

 Max tension limit: 20,000 lbs or 50 percent of rated strength of conductor, whichever is smaller.

Custom milled to: .875-2.50 inch dia.

Bolt size: 3/4 inch steel Bale: 3/4 inch steel Final Torque: 75 ft-lb

Body: Extruded aluminum

Weight: 68 lbs. (30.84kg)

P/N 74155-0875 9 Bolt Pocketbook Grip

The Pocketbook grip for the sagging of wire up to an initial sag-tension, also used during clipping operations. A self-contained unit with no loose parts. Clamp down bolts are peened so flange nuts will not be lost when opened for installation. GMP keeps a solid inventory of components on hand ready to be custom-milled to your requirements ensuring fast delivery to keep your projects on deadline. Please call GMP at 215-357-5500 with your configuration. IMPORTANT: Please provide us with the conductor type, code word, outside diameter and rated strength. For example: ACSS/AW, Cardinal, 1.196", 24600 lb. Orders typically ship in 2-5 days. Our grips are modeled from industry standard.

Pocketbook grips are custom milled and not returnable product.

TOOLS BUILT TO GO THE DISTANCE