

GMP DUCT RODDERS



GMP duct rodders now come standard with length markings every 2 feet and large airless tires on our large rodders for enhanced stability on rough and uneven surfaces.

Continuous Duct Rodders

GMP offers durable and high-performing duct rodders at great value. The bright orange rods are designed for strength, stiffness, and flexibility, proven reliable through years of use.

These tools are essential for underground tasks like cleaning, locating ducts, threading lines, or pulling cables.

Each rodder has a male threaded fitting and tapered head at the front, with a female threaded fitting at the back. The carriers are made of corrosion-resistant steel, with larger ones featuring wheels for easy transport and a hand brake for control.

They are available in standard or toneable versions, with 3/8 and 1/2-inch options.



SPECIFICATIONS

Nominal Size	End Threads	Rated Pull strength	Min Bend Radius
1/4" (6.7mm)	5/16-18	500 lbs.-f (2.2kN)	7.4" (188mm)
3/8" (9mm)	3/8-16	1400 lbs.-f (6.2kN)	9" (230mm)
1/2" (12mm)	3/8-16	1800 lbs.-f (8.0kN)	18" (450mm)



1/2 IN DUCT RODDER



3/8 IN DUCT RODDER

ORDERING INFORMATION

P/N		Duct Rodder Sizes		P/N		Duct Rodder Sizes	
Std. Rod	Tonable			Std. Rod	Tonable		
89202	N/A	1/4" (6.7mm)	X 100 ft (30m)	90244	N/A	3/8" (9mm)	X 1400 ft (427m)
89204	N/A	1/4" (6.7mm)	X 200 ft (61m)	90245	N/A	3/8" (9mm)	X 1500 ft (457m)
89206	N/A	1/4" (6.7mm)	X 300 ft (91m)	90246	N/A	3/8" (9mm)	X 1600 ft (488m)
89208	N/A	1/4" (6.7mm)	X 400 ft (122m)	90247	N/A	3/8" (9mm)	X 1700 ft (518m)
89210	N/A	1/4" (6.7mm)	X 500 ft (152m)	90248	N/A	3/8" (9mm)	X 1800 ft (549m)
90222	91222	3/8" (9mm)	X 200 ft (61m)	90249	N/A	3/8" (9mm)	X 2000 ft (610m)
90224	91224	3/8" (9mm)	X 300 ft (91m)	90252	91252	1/2" (12mm)	X 200 ft (61m)
90226	91226	3/8" (9mm)	X 400 ft (122m)	90254	91254	1/2" (12mm)	X 300 ft (91m)
90228	91228	3/8" (9mm)	X 500 ft (152m)	90256	91256	1/2" (12mm)	X 400 ft (122m)
90230	91230	3/8" (9mm)	X 600 ft (183m)	90258	91258	1/2" (12mm)	X 500 ft (152m)
90232	91232	3/8" (9mm)	X 700 ft (213m)	90260	91260	1/2" (12mm)	X 600 ft (183m)
90234	91234	3/8" (9mm)	X 800 ft (244m)	90262	91262	1/2" (12mm)	X 700 ft (213m)
90236	91236	3/8" (9mm)	X 900 ft (274m)	90264	91264	1/2" (12mm)	X 800 ft (244m)
90238	91238	3/8" (9mm)	X 1000 ft (305m)	90266	91266	1/2" (12mm)	X 900 ft (274m)
90240	N/A	3/8" (9mm)	X 1100 ft (335m)	90268	91268	1/2" (12mm)	X 1000 ft (305m)
90242	N/A	3/8" (9mm)	X 1200 ft (366m)	90270	91270	1/2" (12mm)	X 1100 ft (335m)
90243	N/A	3/8" (9mm)	X 1300 ft (396m)	90272	91272	1/2" (12mm)	X 1200 ft (366m)

Roller Guide for 3/8" (9mm) & 1/2" (12mm) Duct Rodders

The Roller Guide helps guide the duct rod around bends, sweeps and duct misalignments. Can also be used where a duct is already occupied with a cable. 2 1/4" wide.

P/N 89360 Wt. 7.36 oz. (.21kg)



Male & Female Fitting Repair Kits

Used as a replacement if the end fittings break off. Epoxy and installation instructions included.




Std. Rod	Toneable	Description	Wt.
89411	N/A	1/4" (6.7mm) Male	.48 oz. (.01kg)
89412	N/A	1/4" (6.7mm) Female	.48 oz. (.01kg)
89413	88413	3/8" (9mm) Male	3.96 oz. (.11kg)
89414	88414	3/8" (9mm) Female	4.46 oz. (.13kg)
89415	88415	1/2" (12mm) Male	2.97 oz. (.08kg)
89416	88416	1/2" (12mm) Female	3.47 oz. (.10kg)
89398	89398	Epoxy	2 oz. (.06kg)

Flexible Leader

The Flexible Leader is another tool used to guide the duct rod around bends, sweeps and duct misalignments.

P/N 89371 1/4" (6.7mm) Wt. 1 oz. (.03kg)

P/N 89370 3/8" (9mm) & 1/2" (12mm) Wt. 2.24 oz. (.06kg)



Splice Kit

Includes Epoxy, sandpaper, an inline splice and instructions to repair broken Duct Rodders.



Std. Rod	Toneable	Description	Wt.
89417	N/A	1/4" (6.7mm)	1.76 oz. (.05kg)
89418	88418	3/8" (9mm)	2.88 oz. (.08kg)
89419	88419	1/2" (12mm)	2.40 oz. (.07kg)

Shackle Fitting

3/8" (9mm) & 1/2" (12mm) Shackle Fitting is used with our Tapered Heads to provide a larger pulling loop for attaching the pulling line or rope.

P/N 09339 Wt. .80 oz. (.02kg)



Swivel Coupling

The Swivel Couplings connect two duct rods when one length of duct rod is not long enough for the full conduit run. Also provides a rotating swivel when pulling line, wire or rope.

P/N 89380 1/4" (6.7mm)

Wt. .48 oz. (.01kg)

P/N 89382 3/8" (9mm) & 1/2" (12mm)

Wt. 4.32 oz. (.12kg)



Duct Rodder Accessory Kits

These kits come complete with the everyday essentials you'll need for your rodding. Easily attached to the frame with UV treated tie wraps, the Cordura Nylon pouch has plenty of room to store your accessories and keep them with the rodder where they belong.

P/N 89424 Kit for 1/4"
P/N 89425 Kit for 3/8"
P/N 89426 Kit for 1/2"



Tapered Heads

P/N 89350 1/4" (6.7mm) Wt. .16 oz. (.01kg)

P/N 89352 3/8" (9mm) & 1/2" (12mm) Wt. .48 oz. (.12kg)




Sonde Adapters

P/N 89384 Male 1/4" x 20 Wt. 2.08 oz. (.06kg)

P/N 89394 Female M10 x 1.5 Wt. 1.76 oz. (.05kg)

Sonde adapters will only work with 3/8" (9mm) and 1/2" (12mm) duct rodders. Other adapters are available upon request.



Traceable Rod Detection

GMP offers a complete rod detection system along with a 33 khz Sonde for use on our traceable 3/8" and 1/2" rodders. Call for details.



3/16 Inch Continuous Duct Rodders

Ideal for running conduit both inside and outside drops, as well as home drops from hand-hole boxes to buildings. Its design supports pulling duct. The included accessory kit has a flexible leader, replacement ends, swivel coupling, tapered head and a carrying pouch, enhancing its versatility and convenience.

P/N	3/16 in. (4.5mm) Duct Rodders	Weight
89280	3/16 in. X 150 ft.	8.3 lbs. (3.8kg)
89281	3/16 in. X 200 ft.	9.0 lbs. (4kg)
89282	3/16 in. X 250 ft.	9.8 lbs. (4.4kg)
89283	3/16 in. X 300 ft.	11.3 lbs. (5.1kg)