

### Steel Case P/N 89620 (Included)

(Not intended for use as shipping container)  
Weight 36 lbs. (16.3 kg)

### Universal Bracket P/N 89622 (Included)

May be used as a flat mounted angle bracket, or pole mounted using the chain binders  
Weight 26 lbs. (11.8 kg)



### Rope Lock Device P/N 89621 (included)

Eliminates the need to tie off the rope  
Weight 2 lbs. (.9 kg)



Universal Bracket  
Shown with P/N 89600 mounted

### Electric Capstan Hoist and Foot Switch (Included) P/N 89600

Weight 48 lbs. (21.8 kg)

### Hitch Mount

P/N 89623 (optional extra)  
Fits standard 2" utility trailer hitch  
Used with Universal Bracket  
Weight 38 lbs. (17.2 kg)



### SAFETY FEATURES:

- 1,000 lb. capacity (454 kg)
- Lightweight (only 38 lbs. (17.2 kg) w/o universal bracket)
- Power Source: 115 Volt AC
- 40 ft./min (12 m/min) Rope Speed @ 1,000 lb.(454 kg) load
- Remote Foot Control Switch included
- Steel capstan drum with larger radius at load-line wrap and zinc-plated rope surface.

### SIMPLIFY HEAVY TASKS:

- Raising Transformers
- Hoisting Heavy Insulators
- Stringing and Tensioning
- Setting Utility Poles
- Pulling Underground Cable



Typical hoist setup