





BLOWN FIBER INSTALLATION

With the new **GMP Gentle Air**, placing blown fiber couldn't be safer and easier. Built with simplicity and reliability in mind, this blower is driven by an off-the-shelf battery powered drill. Coupled with the driven roller is a precision clutch which you can dial in to your custom torque settings.

The Gentle Air offers battery powered cable speed and distance counter along with a family of useful accessories.

SPECIFICATIONS

Cable size: 0.039" to 0.118" (1.0 to 3.0mm) Tube size: (OD) 0.158" to 0.275" (4 to 7mm) Cable speed: 0-300 ft/min (0-90 m/min) Maximum air pressure: 220 psi. (15 bar) Power requirements: Variable Speed Drill with adjustable torque Weight: 12 lbs. Approx. (5.4Kgs Approx.) Dimensions: (ht x length x width) 8.1" x 9.7" x 8.5" (206mm x 246mm x 216mm)

The Gentle Air is in a league of its own in versatility and value. Backed by the General Machine Products brand that's been a leader in the field since 1936.

TOOLS BUILT TO GO THE DISTANCE

ORDER P/N 89916

General Machine Products (KT), LLC · 3111 Old Lincoln Highway Trevose, PA 19053 USA Tel: +1.215.357.5500 Fax: +1.215.357.6216 www.GMPtools.com