

## Whisper Cable Blowing Machine

Now you can depend on the same GMP quality as our larger machines in a new smaller package...

The Whisper installs microcable and its versatility saves you money.

The design of the Whisper provides for quick and easy component changes for different cable or duct sizes. Its compact size and portable maneuverability make the Whisper ideally suited for either outside or in-building use.

The Whisper uses compressed air to install the cable. The drive roller, powered by most types of cordless drills (not included), control the microfiber as it is propelled into the microduct. An electronic monitoring system provides read-outs of speed and distance.

### Main Features

- Installs cable diameters of 2-8.5mm
- Flat Drop compatible. Call for details
- Accommodates microduct sizes of 4-18mm
- Uses most any variable speed 3/8" drill as a power source
- Light weight, durable construction with precision machined parts
- Single person operation
- Digital cable speed and length monitoring
- Integral air valve and pressure gauge
- Low maintenance
- Ideal for smaller jobs where a bigger machine is simply too much
- Travel bag included

**P/N 89910** Whisper Blowing Machine for round fiber  
**P/N 89897** Plus for round fiber (comes with 3 cable and seal sizes)  
**P/N 89915** Whisper Blowing Machine for flat drop fiber  
**P/N 89895** Plus for flat drop fiber (come with 3 cable and seal sizes)

**P/N 90064** Max (Includes everything for flat drop and round)

### Air Compressor For Micro Fiber Cable Blowing Machines

The Air Compressor is designed specifically for use with our Micro Fiber Cable Blowing Machines. This reliable & efficient screw compressor, powered by a gasoline engine, provides a maximum working pressure of 220 psi (15 bar) with 35.3 cfm (1000 liters/m) flow. The compressor includes an after-cooler and water separator. The output air is filtered and conditioned to optimize the performance of our micro fiber cable blowing machines. The compressor package includes a hose that connects the compressor to the after-cooler and 50 foot 3/4" diameter air hose for after-cooler connection to the microfiber cable blowing machine.

Engine:	Honda® 21 hp
Fuel Cap.:	5 gal (20 liters)
Length:	42" (1070mm)
Width:	31" (800mm)
Height:	30" (780mm)
Weight:	487 lbs. (221kg)
	Compressor and After-Cooler

Order: P/N 89011 Weight: 487 lbs. (221kg)



### Specifications:

Cable Diameter:	2-8.5mm Round and various manufactures Flat Drop
Tube Size O.D.:	4-18mm
Cable Speed (Adjustable):	0-300 ft/min (0-90m/min)
Max Air Pressure:	220 psi (15 Bar)
Power Requirement:	Variable Speed Drill
Width:	8.1" (206mm)
Length:	9.7" (246mm)
Height:	8.5" (216mm)
Net Weight:	12 lbs. (5.4kg)



Air Compressor

After-Cooler and Water Separator

Up to 30% savings on accessories when purchasing the Plus or Max

PLUS ROUND  
PLUS FLAT  
MAX

TUBE COLLET AND CLAMP ASSY - Round Fiber & Flat Drop					
CHOOSE ONE SIZE BELOW FOR BASE WHISPER					
89918	4mm O.D.	1			
89919	5mm O.D.	1			
89926	7mm O.D.	1			
89927	8mm O.D.	1			
89920	8.5mm O.D.	1			
89922	10mm O.D.	1			
89923	12mm O.D.	1			
89921	12.7mm O.D.	1			
89928	14mm O.D.	1			
89925	16mm O.D.	1			
89924	18mm O.D.	1			
CABLE SEAL COLLET ASSY - Round Fiber					
CHOOSE ONE SIZE DUCT SEAL BELOW FOR BASE WHISPER					
89932	3.0 - 3.8mm	1			
89933	3.8 - 5.0mm	1			
89934	5.0 - 6.4mm	1			
89935	6.4 - 8.5mm	1			
CABLE SEAL COLLET ASSY - Flat Drop for Base unit					
CHOOSE ONE SIZE DUCT SEAL BELOW FOR BASE WHISPER FLAT DROP BASE					
89841	Fujikura 24 ct. Drop	1			
89911	Essex	1			
89951	Corning ROC	1			
89952	Corning SST	1			
89954	Corning ROC Fast Access	1			
89956	Commscope	1			
FLAT DROP COMPONENTS for 89897, 90064 and 89895					
89502	SEAL COMSCOPE TONEABLE 3/PK	1			
89505	SEAL SST/COMSCOPE NON-TONE 3/PK	1			
36508	GUIDE SEAL LOWER FAST ACCESS	1			
36509	GUIDE SEAL UPPER FAST ACCESS	1			
37726	SEAL FUJIKURA 24-CT TONE 3/PK	1			
37730	GUIDE SEAL HALF FUJI 24CT DROP	2			
34671	GUIDE SEAL HALF ROC DROP FIBER	2			
36067	BLOCK BEARING DRIVE ROC DROP	2			
37265	INSERT GUIDE INF ROC WHISPER	2			
89506	SEAL CABLE ROC TONEABLE 3/PK	1			
89507	SEAL CABLE ROC NON-TONEBL 3/PK	1			
34059	GUIDE SEAL HALF SST DROP FIBER	2			
36068	BLOCK BEARING DRIVE SST DROP	2			
89504	SEAL CABLE SST TONEABLE 3/PK	1			
03055	BEARING JAF 88500	4			
34258	SCAP M3X8 SKT S/S	2			
34259	SCAP M3X25 SKT S/S	2			
34271	SCAP M2.5X6MM SK SS	2			
36065	ROLLER DRIVE STRAIGHT KNURL	1			
36066	GUIDE INFEEED DROP FIBER	1			
36069	SCAP M6X25 SK SS A	2			
89910	BLOWER MICRO FIBER WHISPER	1			

Spare Tube Seals O Ring (5 Pack)	
89556	4mm
89549	5mm
89553	7mm
89550	8-8.5mm
89551	10mm
89552	12-12.7mm
89555	14mm
89554	16mm
89558	18mm

Spare Cable Seals (5 Pack)	
89511	3-3.8mm
89512	3.8-5mm
89513	5-6.4mm
89514	6.4-8mm
89515	8-8.5mm

**Supplied With All Machines**

- Whisper Cable Blowing Machine
- (2) 9V Lithium Batteries
- Toolkit
- Travel bag
- Manual



**Round Cable**



Tube Collet and Clamp Assemblies



Cable Seal Collet Assemblies

**Flat Drop**



Tube Collet and Clamp Assemblies



Cable Seal Collet Assemblies

\* Fast Access uses above cable guide half.



Unit powered by customer supplied variable speed drill



Tripod Mount  
P/N 89945



Bottled Nitrogen Kit  
P/N 89742



Whisper Air Supply Hose  
P/N 89949



Drill Stand  
P/N 89948

**How To Chose Your WHISPER Component Kits**

**When choosing the Plus Model: (included in price)**

Receive all components to blow the 3 most popular sizes round and flat drop

**When choosing the Max Model: (included in price)**

Nothing to pick, you'll receive one of everything for round and flat drop

**How To Chose Your Whisper Flat Drop Component Kits**

**When choosing the Plus Model: (included in price)**

Receive all components to blow the 3 most popular sizes

GENERAL MACHINE PRODUCTS (KT), LLC  
3111 OLD LINCOLN HWY, TREVOSE PA 19053  
GMPTOOLS.COM 215.357.5500