

# GMP BLOWING MACHINE COMPARISON



	Storm	MicroDrive	Gentle Air	AccelAir 3	Whisper	Whisper Flat Drop	AirStream	Hurricane	JetStream®	Tornado
<b>Cable Diameter:</b>	8 - 3mm (.03 - .118")	2.6 - 5mm (0.102 - 0.196")	1.0 - 3.0mm (0.039 - 0.118")	.8 - 5.0mm (.03 - .20")	3 - 8.5mm (.11 - .33")	call factory	2.5 - 11mm (.10 - .43")	2.5 - 14mm (.10 - .55")	<sup>3</sup> 4 - 20mm (.6 - .79")	<sup>1</sup> 5.84 - 34mm (.23 - 1.34")
<b>Tube Size (O.D.):</b>	5.0, 7.0, 8.0mm	7.0, 8.0, 8.5, 10.0, 12.0, 12.7, 14.0mm	4 to 7mm (0.158 to 0.275")	3 - 12mm (.12 - .47")	4 - 18mm (.15 - .63")	4 - 18mm (.15 - .63")	5-18mm (.20 - .71")	5 - 25mm (.20 - .98")	10 - 50mm O.D. (.75 - 1.50" SDR)	12 - 63mm O.D. (.75 - 2.00" SDR)
<b>Flat Drop Compatible</b>	No	No	No	No	Yes, with optional kit	Yes	Yes	Yes	No	No
<b>EABF® Compatible</b>	No	Yes	No	No	No	No	No	No	No	No
<b>Cable Speed (Adjustable):</b>	0 - 328 ft/min (0 - 100 m/min)	0 - 300 ft/min (0 - 90 m/min)	0 - 300 ft/min (0 - 90 m/min)	0 - 165 ft/min (0 - 50 m/min) with buckle detection  0 - 328 ft/min (0 - 100 m/min) no buckle detection	0 - 300 ft/min (0 - 90 m/min)	0 - 300 ft/min (0 - 90 m/min)	0 - 262 ft/min (0 - 80 m/min)	0 - 280 ft/min (0 - 85m/min)	0 - 280 ft/min (0 - 85 m/min)	0 - 300 ft/min (0 - 90 m/min)
<b>Max Air Pressure/ Volume:</b>	220 psi (15 bar) 35 cfm (1 m³/min)	220 psi (15 bar) 35 cfm (1 m³/min)	220 psi (15 bar) 35 cfm (1 m³/min)	220 psi (15 bar) 8.5 cfm (.24 m³/min)	220 psi (15 bar) 35 cfm (1 m³/min)	220 psi (15 bar) 35 cfm (1 m³/min)	220 psi (15 bar) 35 cfm (1 m³/min)	220 psi (15 bar) 150 - 450 cfm (12 m³/min)	<sup>2</sup> 220 psi (15 bar) 150 - 450 cfm (12 m³/min)	<sup>2</sup> 175 psi (12 bar) 150 - 450 cfm (4 - 12 m³/min)
<b>Drive:</b>	Drive Wheel	Drive Wheel	Drive Roller	Drive Wheel	Drive Roller	Drive Roller	Belts	Belts	Belts	Belts
<b>Power:</b>	DeWalt 20v Battery	Vari Speed Drill	Vari Speed Drill	110/220 VAC or Battery	Vari Speed Drill	Vari Speed Drill	110/220 VAC	110/220 VAC	Gas/Hydraulic	Gas/Hydraulic
<b>Cable Safety</b>	Electronic Torque Control	Magnetic Torque Control	Friction Torque Control	Buckle Protection	Torque Control via Drill	Torque Control via Drill	Electronic Torque Control	Electronic Torque Control	Hydraulic Pressure Sensing	Hydraulic Pressure Sensing
<b>Length:</b>	11.8" (300mm)	5.6" (143mm)	9.7" (246mm)	4.7" (120mm)	9.7" (246mm)	9.7" (246mm)	18.1" (460mm)	21.6" (550mm)	24.5" (620mm)	42" (1070mm)
<b>Width:</b>	4.3" (110mm)	9.7" (248mm)	8.1" (206mm)	7.2" (184mm)	8.1" (206mm)	8.1" (206mm)	11.8" (300mm)	12.2" (310mm)	19" (484mm)	27" (690mm)
<b>Height:</b>	13" (330mm)	6.6" (169mm)	8.5" (216mm)	6.5" (166mm)	8.5" (216mm)	8.5" (216mm)	10.6" (270mm)	13.8" (350mm)	9.2" (233mm)	48.5" (1230mm)
<b>Weight:</b>	4 lbs (1.8Kg)	6 lbs. (3.1kg)	12 lbs. (5.4kg)	6.6 lbs. (3kg)	12 lbs. (5.4kg)	12 lbs. (5.4kg)	33 lbs. (15kg)	53 lbs. (24kg)	68 lbs. (31kg)	155 lbs. (70kg)
<b>P/N – Base</b>	91000	89850	89916	89601	89910	89915	89300	90000	89950	89000
<b>P/N – Plus</b>	92000	-----	89901	-----	89897	89895	89321	90055	90058	89099
<b>P/N – Max</b>	92000-MAX	-----	-----	-----	90064	-----	89327	90054	90059	89113

Base outfitted blowers come with 1 cable and seal size  
 Plus outfitted blowers come with 3 most popular cable and seal sizes  
 Max outfitted blowers come with every available cable and seal size

- <sup>1</sup> Micro duct (10,12 & 12.7mm O.D.) blowing available with add-on kit
- <sup>2</sup> Airflow is duct size dependent
- <sup>3</sup> 4 - 6mm fiber blowing requires a dedicated belt

Up to 30% savings on accessories when purchasing the Plus or Max



General Machine Products (KT), LLC  
 3111 Old Lincoln Hwy, Trevose, PA 19053  
 www.gmptools.com 215-357-5500