


**No emissions
and easy to use**



**Motor Assembly
Order P/N 71490**

**Ground Stand Kit
Order P/N 71498**



**Hitch Mount Stand Kit
Order P/N 71499**

shown with optional hitch mount

**Clean and quiet operation is
the hallmark of the eCapstan.**
Up to 900 lbs of pulling force
this tool will work all day on a
single charge.

FEATURES AND BENEFITS

- QUIET operation improves jobsite communication and safety
- 15,000 ft of cable pulling on a single battery charge*
- NO engine, NO emissions
- Adjustable pulling force and speed
- Electronically controlled pulling setpoints from 0-900+ lbs
- 1 Man Operation
- Data recording of pull force during operation
- Hitch mount or ground stand capable
- Uses capstans from 25" up to 42"
- Quick push button operation to set capstan diameter, max pulling force, and pulling speed
- Winch mode pull force override if pull force setpoint cannot complete pull
- Battery life well over 2000 full charging cycles
- Uses safe LiFePO4 technology

*Estimated based on average pull and average speed, exact distance per charge may vary

3

CONFIGURING YOUR eCAPSTAN

SELECT 1 OF EACH	PART NUMBER	DESCRIPTION
1	71490	eCAPSTAN
↓		
2	36207 71491	32" CAPSTAN 42" CAPSTAN
↓		
	71499 71498	HITCH MOUNT STAND GROUND STAND

PART OF THE GMP

ePowered
LINE OF PRODUCTS

SPECIFICATIONS

Operating Capacities

Max Pulling Load: 900 lbs. (4000 N)@ 100lb setpoints
Max Pulling Speed: 250 feet/minute (76m/min)

Battery

Battery Type: LiFePO4
Battery Size: 48V, 40Ah
Charge Time: 8hr
Height: 11 in (280mm)
Length: 15 in (381mm)
Width: 9 in (229mm)
Weight: 43 lbs. (19.5kg)

Operating Range

Discharge Temperature -4°F to 130°F (-20°C to 54°C)
Charge Temperature 32° F to 114° F (0°C to 46°C)
Storage Temperature 20° F to 95° F (-7°C to 35°C)

Replacement Parts and Accessories

40 Ah battery Pack- **PN 71492**
Trigger controller with cord and plug- **PN 71493**
eCapstan power cord- **PN 71494**
Battery Charger- **PN 71495**
Capstan mounting bolts (6 pack)- **PN 71496**
Capstan mounting nuts (6 pack) -**PN 71497**
Foot Pedal controller with cord - **PN 71800**
Foot Pedal replacement cord - **PN 38536**

15 AMP HIGH SPEED BATTERY CHARGER

Will charge the eCapstans battery in half the time of the standard charger. **P/N 71496**



Foot Pedal controller with cord - PN 71800

FOOT PEDAL CONTROLLER ACCESSORY

Allows the user to work hands-free at a safe distance. **P/N 71800**

- Variable Speed
- 15 ft heavy-duty cord
- Foot operated forward and reverse
- Durable powder-coated frame
- Designed to be used in damp environments

Dimensions - Tool Only

Height: 15.5 in (394mm)
Length: 25" (635mm)
Width: 14" (356mm)
Weight: 180 lbs. (82kg)

Dimensions - With Ground Stand and 42 inch Capstan

Height: 53 in (1346mm)
Length: 46.75 in (1187mm)
Width: 48.5 in (1232mm)
Weight: 326 lbs. (147kg)

Dimensions - With Hitch Mount and 42 inch Capstan

Height: 43 in (1092mm)
Length: 53 in (1346mm)
Width: 24 in (609mm)
Weight: 258 lbs. (117kg)



15 Amp high speed charger - PN 71496

PART OF THE GMP

Powered
LINE OF PRODUCTS